

## ULTRA-SLIM PROXIMITY READER - PT 1000



**IFSEC 2007  
SHOW OFFER  
£58 ea.  
+VAT**

The ULTRA-SLIM PT 1000 proximity reader allows for simple installation and configuration into virtually any application. The PT 1000 incorporates advanced encrypted coding of user keys. The extremely high IP (67) rating enables the PT1000 to be mounted in exposed external environments. The durable, wipe clean face incorporates LED indicators to assist the user.

Manufactured to the highest standard and offering reliable operation, the PT1000 is compatible with entire RTR range of locking devices via our supplementary relays and ancillary power supply units. The PT1000 is suitable for connection to existing access control systems or is ideal as part of a stand-alone system.



For further advice on compatibility, contact our technical team.

The optional mounting bezel is ideal for added physical protection against mechanical damage.

Replacement reader faceplates are available to order.



### Specifications

#### Finish

- Proximity reader - Black (White optional)
- Mounting plate - Stainless steel

#### Dimensions

- 130mm (h) x 50mm (w) x 8mm (d)

#### Power Supply & Output

- 9 - 17 Volts DC (30mA consumption)
- Output - Yellow core max. 500mA
- Output - White core max. 500mA
- External control buzzer Red & Green LED
- External control buzzer Hold and Lock

#### Operating Temperatures

- -30°C to +80°C
- Humidity 100%
- IP67 rating

#### Cable (supplied)

- 8 core signal x 2500mm

#### Accessories

- Mounting bezel - Anodised aluminium
- Replacement reader faceplate

## ULTRA-SLIM KEYPAD - CT 1000



The ULTRA-SLIM CT 1000 keypad allows for simple installation and configuration into virtually any application. The CT 1000 incorporates advanced functionality in allowing 4-DIGIT and 8-DIGIT key combinations for differing security operation. The extremely high IP (67) rating enables the CT1000 to be mounted in exposed external environments. The clearly marked keypad is durable, wipe clean and incorporates LED indicators to assist the user.

Manufactured to the highest standard and offering reliable operation, the CT1000 is compatible with entire RTR range of locking devices via our supplementary relays and ancillary power supply units.



For further advice on compatibility, contact our technical team.

The optional mounting bezel is ideal for added physical protection against mechanical damage, security and mounting points.

Replacement keypad faceplates are available to order.



### Specifications

#### Finish

- Keypad - Black (White optional)
- Mounting plate - Stainless steel

#### Dimensions

- 130mm (h) x 50mm (w) x 8mm (d)

#### Power Supply & Output

- 9 - 17 Volts DC (30mA consumption)
- Output - Yellow core max. 500mA
- Output - White core max. 500mA
- External control buzzer Red & Green LED
- External control buzzer Hold and Lock

#### Operating Temperatures

- -30°C to + 80°C
- Humidity 100%
- IP67 rating

#### Cable (supplied)

- 8 core signal x 2500mm

#### Accessories

- Mounting bezel - Anodised aluminium
- Replacement keypad faceplate